

## EU- (EC-) declaration of conformity

### to directive 2014/34/EU (94/9/EC)

We hereby declare, that the delivered solenoid valves \*)

- in combination with valve solenoids of series  
80xx, 81xx, 83xx, 84xx, 91xx, 92xx, 93xx, 94xx, 95xx  
in combination with the mounted socket 1262390 or with the ATEX retrofit kit  
1262560 marked:

 II 3G Ex nA IIB T4 Gc

 II 3D Ex tc IIIB T130 °C Dc IP65

conform to the requirements of directive 2014/34/EU (94/9/EC) for use as intended in potentially explosive atmospheres.

The solenoids have been developed and designed to the following harmonised standards:

- EN 60079-0:2014 — Electrical apparatus for explosive gas atmospheres — Part 0: General requirements
- EN 60079-15:2011 — Electrical apparatus for explosive gas atmospheres — Part 15: Construction, test and marking of type of protection “n” electrical apparatus
- EN 60079-31:2013 — Explosive atmospheres — Part 31: Equipment dust ignition protection by enclosure „t“
- EN 60529:2014 — Degrees of protection provided by enclosures (IP code)
- EN 13463-1:2009 — Non-electrical equipment for potentially explosive atmospheres — Part 1: Basic method and requirements (Valves are not marked as no mechanical ignition sources were found during risk analysis).

### \*) Caution

Valves from DN 65 and up additionally require secure connection between valve casing and the unit's equipotential bonding! The maximum surface temperature of the body depends on the fluid and the ambient temperatures and must be below the ignition temperature.

  
Oliver Wehking  
Managing Director

  
Eckhard Euscher  
Representative

Bad Oeynhausen, 5 April 2016

**IMI**  
Precision Engineering

Engineering  
GREAT  
Solutions

 IMI NORGRN

 IMI BUSCHJOST

 IMI FAS

 IMI HERION

 IMI MAXSEAL