


- > **Port size: G1/4**
- > **Robust corrosion resistant construction**
- > **Dustproof and water ingress protected**
- > **Position of levers may be adjusted**



### Technical features

**Medium:**

Compressed air, filtered, lubricated and non-lubricated

**Operation:**

Poppet valve, directly actuated

**Mounting:**

Through-holes in valve body

**Port size:**

G1/4

**Operating pressure:**

NC 0,7 ... 10 bar (10 ... 145 psi)

NO 0,7 ... 7 bar (10 ... 101 psi)

**Flow characteristics**

**'1' » '2':**

Cv	Kv	l/min
1,28	1,11	1258

**'2' » '3':**

Cv	Kv	l/min
0,86	0,74	844

**Ambient/Media temperature:**


-40 ... +75°C (-40 ... +167°F)

Air supply must be dry enough to avoid ice formation at temperatures below +2°C (+35°F).

**Materials:**

Body, poppet and lever: brass  
Screws and roller: stainless steel  
Seals: low NBR

### Technical data

Symbol	Port size	Operator/return	Operating pressure (bar)	Operating force at 0,7 bar	Operating force at 10 bar	Weight (kg)	Spares kit	Drawing No.	Model
	G1/4	Roller/spring	0,7 ... 10	1,5 Nm	1,8 Nm	0,77	SLV/15293/00	1	SLV/15293/A

