



### Revision List

referred to on Certificate No.: 968/V 1139.01/22  
**Certified Product: Electromagnetic Control Valves with Safety Function, Series 97105xx**



#### Safety related modules / components

Type Designation	Description	HW / SW Revision	Report-No.:	Certification Status																																																																																																																																																																																																																															
Series 971 (0/3) (2/3/4/5/6/7) xx	<p>Electromagnetic control valves with safety function</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Base type</th> <th>Function</th> <th>Material</th> <th>Port</th> <th>Version</th> </tr> </thead> <tbody> <tr> <td></td> <td>971</td> <td>x</td> <td>x</td> <td>x</td> <td>x</td> </tr> <tr> <td>5/2-way spring return</td> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3/2-way spring return</td> <td></td> <td>3</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="6">Chemistry-version to -25 °C...+65 °C or 0 °C...+80 °C</td> </tr> <tr> <td>Aluminum</td> <td></td> <td></td> <td>2</td> <td></td> <td></td> </tr> <tr> <td>Brass</td> <td></td> <td></td> <td>3</td> <td></td> <td></td> </tr> <tr> <td>Stainless steel</td> <td></td> <td></td> <td>4</td> <td></td> <td></td> </tr> <tr> <td colspan="6">Chemistry-version to -40 °C...+40 °C</td> </tr> <tr> <td>Aluminum</td> <td></td> <td></td> <td>5</td> <td></td> <td></td> </tr> <tr> <td>Brass</td> <td></td> <td></td> <td>6</td> <td></td> <td></td> </tr> <tr> <td>Stainless Steel</td> <td></td> <td></td> <td>7</td> <td></td> <td></td> </tr> <tr> <td>G1/4 NAMUR for rotary actuator</td> <td></td> <td></td> <td></td> <td>0</td> <td></td> </tr> <tr> <td>1/4 NPT NAMUR for rotary actuator</td> <td></td> <td></td> <td></td> <td>1</td> <td></td> </tr> <tr> <td>G1/4 NAMUR for linear actuator</td> <td></td> <td></td> <td></td> <td>2</td> <td></td> </tr> <tr> <td>G1/4</td> <td></td> <td></td> <td></td> <td>3</td> <td></td> </tr> <tr> <td>1/4 NPT</td> <td></td> <td></td> <td></td> <td>4</td> <td></td> </tr> <tr> <td>G1/2</td> <td></td> <td></td> <td></td> <td>5</td> <td></td> </tr> <tr> <td>1/2 NPT</td> <td></td> <td></td> <td></td> <td>6</td> <td></td> </tr> <tr> <td>G1/2 NAMUR for rotary actuator</td> <td></td> <td></td> <td></td> <td>9</td> <td>4</td> </tr> <tr> <td>1/2 NPT NAMUR for rotary actuator</td> <td></td> <td></td> <td></td> <td>9</td> <td>6</td> </tr> <tr> <td colspan="5">Version without manual override, control air inside</td> <td>5</td> </tr> <tr> <td colspan="5">Version pneumatic controlled</td> <td>8</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Solenoid</th> <th>Type</th> <th>Nominal voltage</th> <th>Nominal current</th> <th>Temperature range</th> </tr> </thead> <tbody> <tr> <td></td> <td>0763</td> <td>DC 24 V</td> <td>78 mA</td> <td>-25...+60 °C</td> </tr> <tr> <td></td> <td>0298</td> <td>DC 24 V</td> <td>301 mA</td> <td>-20...+70 °C</td> </tr> <tr> <td></td> <td>0299</td> <td>AC 230 V</td> <td>18 mA</td> <td>-20...+70 °C</td> </tr> <tr> <td></td> <td>4200</td> <td>DC 24 V</td> <td>33 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>4201</td> <td>AC 230 V</td> <td>26 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>4600</td> <td>DC 24 V</td> <td>33 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>4602</td> <td>DC 24 V</td> <td>33 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>4601</td> <td>AC 230 V</td> <td>26 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>4603</td> <td>AC 230 V</td> <td>26 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>4802</td> <td>DC 24 V</td> <td>33 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>4803</td> <td>AC 230 V</td> <td>6 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>3720</td> <td>DC 24 V</td> <td>59 mA</td> <td>-20...+60 °C</td> </tr> <tr> <td></td> <td>2050</td> <td>≥ DC 8 V</td> <td>≥ 33 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>2051</td> <td>≥ DC 11 V</td> <td>≥ 24 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>2052</td> <td>≥ DC 15 V</td> <td>≥ 17 mA</td> <td>-40...+80 °C</td> </tr> <tr> <td></td> <td>2053</td> <td>≥ DC 19 V</td> <td>≥ 13 mA</td> <td>-40...+80 °C</td> </tr> </tbody> </table>	Type	Base type	Function	Material	Port	Version		971	x	x	x	x	5/2-way spring return		0				3/2-way spring return		3				Chemistry-version to -25 °C...+65 °C or 0 °C...+80 °C						Aluminum			2			Brass			3			Stainless steel			4			Chemistry-version to -40 °C...+40 °C						Aluminum			5			Brass			6			Stainless Steel			7			G1/4 NAMUR for rotary actuator				0		1/4 NPT NAMUR for rotary actuator				1		G1/4 NAMUR for linear actuator				2		G1/4				3		1/4 NPT				4		G1/2				5		1/2 NPT				6		G1/2 NAMUR for rotary actuator				9	4	1/2 NPT NAMUR for rotary actuator				9	6	Version without manual override, control air inside					5	Version pneumatic controlled					8	Solenoid	Type	Nominal voltage	Nominal current	Temperature range		0763	DC 24 V	78 mA	-25...+60 °C		0298	DC 24 V	301 mA	-20...+70 °C		0299	AC 230 V	18 mA	-20...+70 °C		4200	DC 24 V	33 mA	-40...+80 °C		4201	AC 230 V	26 mA	-40...+80 °C		4600	DC 24 V	33 mA	-40...+80 °C		4602	DC 24 V	33 mA	-40...+80 °C		4601	AC 230 V	26 mA	-40...+80 °C		4603	AC 230 V	26 mA	-40...+80 °C		4802	DC 24 V	33 mA	-40...+80 °C		4803	AC 230 V	6 mA	-40...+80 °C		3720	DC 24 V	59 mA	-20...+60 °C		2050	≥ DC 8 V	≥ 33 mA	-40...+80 °C		2051	≥ DC 11 V	≥ 24 mA	-40...+80 °C		2052	≥ DC 15 V	≥ 17 mA	-40...+80 °C		2053	≥ DC 19 V	≥ 13 mA	-40...+80 °C	-	968/V 1139.01/22	<i>Valid</i>
Type	Base type	Function	Material	Port	Version																																																																																																																																																																																																																														
	971	x	x	x	x																																																																																																																																																																																																																														
5/2-way spring return		0																																																																																																																																																																																																																																	
3/2-way spring return		3																																																																																																																																																																																																																																	
Chemistry-version to -25 °C...+65 °C or 0 °C...+80 °C																																																																																																																																																																																																																																			
Aluminum			2																																																																																																																																																																																																																																
Brass			3																																																																																																																																																																																																																																
Stainless steel			4																																																																																																																																																																																																																																
Chemistry-version to -40 °C...+40 °C																																																																																																																																																																																																																																			
Aluminum			5																																																																																																																																																																																																																																
Brass			6																																																																																																																																																																																																																																
Stainless Steel			7																																																																																																																																																																																																																																
G1/4 NAMUR for rotary actuator				0																																																																																																																																																																																																																															
1/4 NPT NAMUR for rotary actuator				1																																																																																																																																																																																																																															
G1/4 NAMUR for linear actuator				2																																																																																																																																																																																																																															
G1/4				3																																																																																																																																																																																																																															
1/4 NPT				4																																																																																																																																																																																																																															
G1/2				5																																																																																																																																																																																																																															
1/2 NPT				6																																																																																																																																																																																																																															
G1/2 NAMUR for rotary actuator				9	4																																																																																																																																																																																																																														
1/2 NPT NAMUR for rotary actuator				9	6																																																																																																																																																																																																																														
Version without manual override, control air inside					5																																																																																																																																																																																																																														
Version pneumatic controlled					8																																																																																																																																																																																																																														
Solenoid	Type	Nominal voltage	Nominal current	Temperature range																																																																																																																																																																																																																															
	0763	DC 24 V	78 mA	-25...+60 °C																																																																																																																																																																																																																															
	0298	DC 24 V	301 mA	-20...+70 °C																																																																																																																																																																																																																															
	0299	AC 230 V	18 mA	-20...+70 °C																																																																																																																																																																																																																															
	4200	DC 24 V	33 mA	-40...+80 °C																																																																																																																																																																																																																															
	4201	AC 230 V	26 mA	-40...+80 °C																																																																																																																																																																																																																															
	4600	DC 24 V	33 mA	-40...+80 °C																																																																																																																																																																																																																															
	4602	DC 24 V	33 mA	-40...+80 °C																																																																																																																																																																																																																															
	4601	AC 230 V	26 mA	-40...+80 °C																																																																																																																																																																																																																															
	4603	AC 230 V	26 mA	-40...+80 °C																																																																																																																																																																																																																															
	4802	DC 24 V	33 mA	-40...+80 °C																																																																																																																																																																																																																															
	4803	AC 230 V	6 mA	-40...+80 °C																																																																																																																																																																																																																															
	3720	DC 24 V	59 mA	-20...+60 °C																																																																																																																																																																																																																															
	2050	≥ DC 8 V	≥ 33 mA	-40...+80 °C																																																																																																																																																																																																																															
	2051	≥ DC 11 V	≥ 24 mA	-40...+80 °C																																																																																																																																																																																																																															
	2052	≥ DC 15 V	≥ 17 mA	-40...+80 °C																																																																																																																																																																																																																															
	2053	≥ DC 19 V	≥ 13 mA	-40...+80 °C																																																																																																																																																																																																																															

IMI International s.r.o.  
 Evropska 852  
 664 42 Modrice / Czech Republic

TUV Rheinland Industrie Service GmbH  
 Automation - Functional Safety & Cyber Security (A-FS & CS)  
 Am Grauen Stein

51105 Köln / Germany



### Revision List

referred to on Certificate No.: 968/V 1139.01/22  
Certified Product: Electromagnetic Control Valves with  
Safety Function, Series 97105xx



#### Manufacturing Locations

Manufacturer	Report-No.:	Certification Status
Norgren GmbH Stuttgarter Str. 120 70736 Fellbach Germany	968/V 1139.00/20	<i>Expired</i>
IMI International s.r.o. Evropska 862 664 42 Modrice Czech Republic	968/V 1139.01/22	<i>Valid</i>

#### Safety Manual / User documentation

Document No.	Description	Report-No.:	Certification Status
7503649000000006	Safety Manual – Rev. B – 2020-09-09	968/V 1139.01/22	<i>Valid</i>

The content of this Revision List has been agreed between Manufacturer and Certification Body.  
**Revision:**

Date	Rev.	Description / Changes	Author
2022-11-15	1.0	Initial creation, based on Report-No.: 968/V 1139.01/22	Komberg / A-FS&CS

IMI International s.r.o.  
Evropska 852  
664 42 Modrice / Czech Republic

TUV Rheinland Industrie Service GmbH  
Automation - Functional Safety & Cyber Security (A-FS & CS)  
Am Grauen Stein

51105 Köln / Germany