



Revision List

referred to on Certificate No.: 968/V 1140.01/23
Certified Product: Electromagnetic Control Valves with Safety Function, Series 980xx



Safety related modules / components

Type Designation	Description	HW / SW Revision	Report-No.:	Certification Status																																																																																																																																																	
Series 98015 & 98025	Electromagnetic control valves with safety function	-	968/V 1140.01/23	<i>Valid</i>																																																																																																																																																	
	<table border="1"> <thead> <tr> <th>Type</th> <th>nominal voltage V</th> <th>nominal output</th> <th>degree of protection</th> <th>ambient temperature °C</th> </tr> </thead> <tbody> <tr><td>0800</td><td>DC 24/48/60/110/200/220</td><td>16 W</td><td>IP65</td><td>-25...+60 °C</td></tr> <tr><td>0801</td><td></td><td></td><td></td><td></td></tr> <tr><td>2050</td><td>DC 24</td><td>min. 33 mA</td><td>IP66 / EEx ia II T5/T6</td><td>-40...+80 °C</td></tr> <tr><td>2051</td><td>DC 24</td><td>min. 24 mA</td><td>IP66 / EEx ia II T5/T6</td><td>-40...+80 °C</td></tr> <tr><td>2052</td><td>DC 24</td><td>min. 17 mA</td><td>IP66 / EEx ia II T5/T6</td><td>-40...+80 °C</td></tr> <tr><td>2053</td><td>DC 24</td><td>min. 13 mA</td><td>IP66 / EEx ia II T5/T6</td><td>-40...+80 °C</td></tr> <tr><td>3720</td><td>DC 12/24</td><td>1,4 W</td><td>XP NEMA 4,4X,6,6P,7,9</td><td>-20...+60 °C</td></tr> <tr><td>3803</td><td>AC 24/110/230</td><td>18 VA</td><td>IP00</td><td>-25...+60 °C</td></tr> <tr><td>3824</td><td>DC 12/24/110</td><td>9 W</td><td>IP65</td><td>-20...+60 °C</td></tr> <tr><td>3825</td><td>AC 110/120/220/230/240 V</td><td>10 W</td><td>IP65</td><td>-20...+60 °C</td></tr> <tr><td>3826</td><td>DC 24</td><td>13 W</td><td>XP NEMA 4,4X,6,6P,7,9</td><td>-20...+60 °C</td></tr> <tr><td>3827</td><td>AC 230</td><td>15 VA</td><td>XP NEMA 4,4X,6,6P,7,9</td><td>-20...+60 °C</td></tr> <tr><td>4200</td><td>DC 24/48/110</td><td>0,8 W</td><td>IP66 / EEx me II T5/T6</td><td>-40...+80/+70 °C</td></tr> <tr><td>4201</td><td>AC 230 AC 110/230</td><td>1,3VA</td><td>IP66 / EEx me II T4/T6</td><td>-40...+80/+55 °C</td></tr> <tr><td>4270</td><td>DC 24</td><td>8 W</td><td>IP66 / EEx me II T4/T6</td><td>-40...+65/55 °C</td></tr> <tr><td>4271</td><td>AC 230 AC 110/230</td><td>10 VA</td><td>IP66 / EEx me II T4/T6</td><td>-40...+65/55 °C</td></tr> <tr><td>4600</td><td>DC 24/48/110</td><td>0,8 W</td><td>IP66 / EEx me II T5/T6</td><td>-40...+70/+80 °C</td></tr> <tr><td>4601</td><td>AC 230 AC 110/230</td><td>1,3VA</td><td>IP66 / EEx me II T4/T6</td><td>-40...+70/+80 °C</td></tr> <tr><td>4602</td><td>DC 24/48/110</td><td>0,8 W</td><td>IP66 / EEx me II T5/T6</td><td>-40...+80/+70 °C</td></tr> <tr><td>4603</td><td>AC 230 AC 110/230</td><td>1,3VA</td><td>IP66 / EEx me II T4/T6</td><td>-40...+ 80/+55 °C</td></tr> <tr><td>4670</td><td>DC 24</td><td>8 W</td><td>IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6</td><td>-40...+65/55 °C</td></tr> <tr><td>4671</td><td>AC 230 AC 110/230</td><td>10VA</td><td>IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6</td><td>-40...+65/55 °C</td></tr> <tr><td>4672</td><td>DC 24</td><td>8 W</td><td>IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6</td><td>-40...+65/55 °C</td></tr> <tr><td>4673</td><td>AC 230 AC 110/230</td><td>10VA</td><td>IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6</td><td>-40...+65/55 °C</td></tr> <tr><td>4872</td><td>DC 24</td><td>8 W</td><td>IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6</td><td>-40...+40/50 °C Stäube T 100 °C</td></tr> <tr><td>4873</td><td>AC 230 AC 110/230</td><td>10 VA</td><td>IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6</td><td>-40...+40/50 °C dust T 100 °C</td></tr> <tr><td>4802</td><td>DC 24</td><td>0,8 W</td><td>IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6</td><td>-40...+70/80 °C dust T 100 °C</td></tr> <tr><td>4803</td><td>AC 230 AC 110/230</td><td>10 VA</td><td>IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6</td><td>-40...+70/80 °C dust T 100 °C</td></tr> </tbody> </table>	Type	nominal voltage V	nominal output	degree of protection	ambient temperature °C	0800	DC 24/48/60/110/200/220	16 W	IP65	-25...+60 °C	0801					2050	DC 24	min. 33 mA	IP66 / EEx ia II T5/T6	-40...+80 °C	2051	DC 24	min. 24 mA	IP66 / EEx ia II T5/T6	-40...+80 °C	2052	DC 24	min. 17 mA	IP66 / EEx ia II T5/T6	-40...+80 °C	2053	DC 24	min. 13 mA	IP66 / EEx ia II T5/T6	-40...+80 °C	3720	DC 12/24	1,4 W	XP NEMA 4,4X,6,6P,7,9	-20...+60 °C	3803	AC 24/110/230	18 VA	IP00	-25...+60 °C	3824	DC 12/24/110	9 W	IP65	-20...+60 °C	3825	AC 110/120/220/230/240 V	10 W	IP65	-20...+60 °C	3826	DC 24	13 W	XP NEMA 4,4X,6,6P,7,9	-20...+60 °C	3827	AC 230	15 VA	XP NEMA 4,4X,6,6P,7,9	-20...+60 °C	4200	DC 24/48/110	0,8 W	IP66 / EEx me II T5/T6	-40...+80/+70 °C	4201	AC 230 AC 110/230	1,3VA	IP66 / EEx me II T4/T6	-40...+80/+55 °C	4270	DC 24	8 W	IP66 / EEx me II T4/T6	-40...+65/55 °C	4271	AC 230 AC 110/230	10 VA	IP66 / EEx me II T4/T6	-40...+65/55 °C	4600	DC 24/48/110	0,8 W	IP66 / EEx me II T5/T6	-40...+70/+80 °C	4601	AC 230 AC 110/230	1,3VA	IP66 / EEx me II T4/T6	-40...+70/+80 °C	4602	DC 24/48/110	0,8 W	IP66 / EEx me II T5/T6	-40...+80/+70 °C	4603	AC 230 AC 110/230	1,3VA	IP66 / EEx me II T4/T6	-40...+ 80/+55 °C	4670	DC 24	8 W	IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6	-40...+65/55 °C	4671	AC 230 AC 110/230	10VA	IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6	-40...+65/55 °C	4672	DC 24	8 W	IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6	-40...+65/55 °C	4673	AC 230 AC 110/230	10VA	IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6	-40...+65/55 °C	4872	DC 24	8 W	IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6	-40...+40/50 °C Stäube T 100 °C	4873	AC 230 AC 110/230	10 VA	IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6	-40...+40/50 °C dust T 100 °C	4802	DC 24	0,8 W	IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6	-40...+70/80 °C dust T 100 °C	4803	AC 230 AC 110/230	10 VA	IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6	-40...+70/80 °C dust T 100 °C			
Type	nominal voltage V	nominal output	degree of protection	ambient temperature °C																																																																																																																																																	
0800	DC 24/48/60/110/200/220	16 W	IP65	-25...+60 °C																																																																																																																																																	
0801																																																																																																																																																					
2050	DC 24	min. 33 mA	IP66 / EEx ia II T5/T6	-40...+80 °C																																																																																																																																																	
2051	DC 24	min. 24 mA	IP66 / EEx ia II T5/T6	-40...+80 °C																																																																																																																																																	
2052	DC 24	min. 17 mA	IP66 / EEx ia II T5/T6	-40...+80 °C																																																																																																																																																	
2053	DC 24	min. 13 mA	IP66 / EEx ia II T5/T6	-40...+80 °C																																																																																																																																																	
3720	DC 12/24	1,4 W	XP NEMA 4,4X,6,6P,7,9	-20...+60 °C																																																																																																																																																	
3803	AC 24/110/230	18 VA	IP00	-25...+60 °C																																																																																																																																																	
3824	DC 12/24/110	9 W	IP65	-20...+60 °C																																																																																																																																																	
3825	AC 110/120/220/230/240 V	10 W	IP65	-20...+60 °C																																																																																																																																																	
3826	DC 24	13 W	XP NEMA 4,4X,6,6P,7,9	-20...+60 °C																																																																																																																																																	
3827	AC 230	15 VA	XP NEMA 4,4X,6,6P,7,9	-20...+60 °C																																																																																																																																																	
4200	DC 24/48/110	0,8 W	IP66 / EEx me II T5/T6	-40...+80/+70 °C																																																																																																																																																	
4201	AC 230 AC 110/230	1,3VA	IP66 / EEx me II T4/T6	-40...+80/+55 °C																																																																																																																																																	
4270	DC 24	8 W	IP66 / EEx me II T4/T6	-40...+65/55 °C																																																																																																																																																	
4271	AC 230 AC 110/230	10 VA	IP66 / EEx me II T4/T6	-40...+65/55 °C																																																																																																																																																	
4600	DC 24/48/110	0,8 W	IP66 / EEx me II T5/T6	-40...+70/+80 °C																																																																																																																																																	
4601	AC 230 AC 110/230	1,3VA	IP66 / EEx me II T4/T6	-40...+70/+80 °C																																																																																																																																																	
4602	DC 24/48/110	0,8 W	IP66 / EEx me II T5/T6	-40...+80/+70 °C																																																																																																																																																	
4603	AC 230 AC 110/230	1,3VA	IP66 / EEx me II T4/T6	-40...+ 80/+55 °C																																																																																																																																																	
4670	DC 24	8 W	IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6	-40...+65/55 °C																																																																																																																																																	
4671	AC 230 AC 110/230	10VA	IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6	-40...+65/55 °C																																																																																																																																																	
4672	DC 24	8 W	IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6	-40...+65/55 °C																																																																																																																																																	
4673	AC 230 AC 110/230	10VA	IP66 / EEx md IIC T4/T6 IP66 / EEx me II T4/T6	-40...+65/55 °C																																																																																																																																																	
4872	DC 24	8 W	IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6	-40...+40/50 °C Stäube T 100 °C																																																																																																																																																	
4873	AC 230 AC 110/230	10 VA	IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6	-40...+40/50 °C dust T 100 °C																																																																																																																																																	
4802	DC 24	0,8 W	IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6	-40...+70/80 °C dust T 100 °C																																																																																																																																																	
4803	AC 230 AC 110/230	10 VA	IP66 / Ex mb d IIC T4/T6 IP66 / Ex mb e II T4/T6	-40...+70/80 °C dust T 100 °C																																																																																																																																																	

IMI International s.r.o.
 Evropska 852
 664 42 Modrice / Czech Republic

TUV Rheinland Industrie Service GmbH
 Automation - Functional Safety & Cyber Security (A-FS & CS)
 Am Grauen Stein

51105 Köln / Germany



Revision List

referred to on Certificate No.: 968/V 1140.01/23
Certified Product: Electromagnetic Control Valves with
Safety Function, Series 980xx



Manufacturing Locations

Manufacturer	Report-No.:	Certification Status
Norgren GmbH Stuttgarter Str. 120 70736 Fellbach Germany	968/V 1140.00/20	<i>Expired</i>
IMI International s.r.o. Evropska 852 664 42 Modrice Czech Republic	968/V 1140.01/23	<i>Valid</i>

Safety Manual / User documentation

Document No.	Description	Report-No.:	Certification Status
7503649000000006	Safety Manual – Rev. B – 2020-09-09	968/V 1140.01/23	<i>Valid</i>

The content of this Revision List has been agreed between Manufacturer and Certification Body.
Revision:

Date	Rev.	Description / Changes	Author
2023-03-30	1.0	Initial creation, based on Report-No.: 968/V 1140.01/23	Komberg / A-FS&CS

IMI International s.r.o.
Evropska 852
664 42 Modrice / Czech Republic

TUV Rheinland Industrie Service GmbH
Automation - Functional Safety & Cyber Security (A-FS & CS)
Am Grauen Stein

51105 Köln / Germany